







SBA							
	Type	Resistance (m Ohm)	Material	Thickness	Tolerance	Power (W)	SIZE
	SBA-Cu-R0000	< 0.1	Tin Plated Copper	0.42mm	1%, 2%, 5%	-	2512
	SBA-C-R0003	0.3	Copper Manganese 38 Alloy	0.95mm	1%, 2%, 5%	3	2512
	SBA-MC2-R0003	0.3	MC2	0.95mm	1%, 2%, 5%	3	2512
	SBA-CM-R0005	0.5	Copper Manganese 43 Alloy	0.85mm	1%, 2%, 5%	3	2512
	SBA-CM-R001	1	Copper Manganese 43 Alloy	0.42mm	1%, 2%, 5%	3	2512
	SBA-CM-R0013	1.3	Copper Manganese 43 Alloy	0.33mm	1%, 2%, 5%	3	2512
	SBA-A1-R002	2	Aluchrom Alloy	0.67mm	1%, 2%, 5%	3	2512
	SBA-A1-R003	3	Aluchrom Alloy	0.45mm	1%, 2%, 5%	2	2512
	SBA-A1-R004	4	Aluchrom Alloy	0.33mm	1%, 2%, 5%	2	2512
	SBA-A1-R005	5	Aluchrom Alloy	0.33mm	1%, 2%, 5%	1.5	2512
SBA-A1-R0068	6.8	Aluchrom Alloy	0.33mm	1%, 2%, 5%	1.5	2512	
SBA-A1-R010	10	Aluchrom Alloy	0.33mm	1%, 2%, 5%	1	2512	

SBB							
	Type	Resistance (m Ohm)	Material	Thickness	Tolerance	Power (W)	SIZE
	SBB-CM-R0002	0.2	Copper Manganese 43 Alloy	1.37mm	1%, 5%	10	5930
	SBB-CM-R0003	0.3	Copper Manganese 43 Alloy	0.91mm	1%, 5%	7	5930
	SBB-CM-R0005	0.5	Copper Manganese 43 Alloy	0.55mm	1%, 5%	6	5930
	SBB-CM-R0006	0.6	Copper Manganese 43 Alloy	0.46mm	1%, 5%	5	5930
	SBB-A1-R001	1	Aluchrom Alloy	0.91mm	1%, 5%	6	5930
	SBB-A1-R002	2	Aluchrom Alloy	0.88mm	1%, 5%	6	5930
SBB-A1-R002	2	Aluchrom Alloy	0.46mm	1%, 5%	4	5930	


SBC							
	Type	Resistance (m Ohm)	Material	Thickness	Tolerance	Power (W)	SIZE
	SBC-C-R0002	0.2	Copper Manganese 38 Alloy	1.20mm	1%, 5%	5	4026
	SBC-C-R0003	0.3	Copper Manganese 38 Alloy	0.85mm	1%, 5%	5	4026
	SBC-C-R0005	0.5	Copper Manganese 38 Alloy	0.42mm	1%, 5%	5	4026
	SBC-CM-R0007	0.7	Copper Manganese 43 Alloy	0.44mm	1%, 5%	4	4026
	SBC-CM-R001	1	Copper Manganese 43 Alloy	0.35mm	1%, 5%	4	4026
	SBC-A1-R002	2	Aluchrom Alloy	0.55mm	1%, 5%	4	4026
SBC-A1-R003	3	Aluchrom Alloy	0.36mm	1%, 5%	3	4026	

SBD							
	Type	Resistance (m Ohm)	Material	Thickness	Tolerance	Power (W)	SIZE
	SBD-CM-R003	3	Copper Manganese 43 Alloy	0.50mm	1%, 2%, 5%	2	3812
	SBD-CM-R005	5	Copper Manganese 43 Alloy	0.30mm	1%, 2%, 5%	2	3812
	SBD-A1-R010	10	Aluchrom Alloy	0.40mm	1%, 2%, 5%	2	3812
	SBD-A1-R015	15	Aluchrom Alloy	0.40mm	1%, 2%, 5%	2	3812
	SBD-A1-R020	20	Aluchrom Alloy	0.30mm	1%, 2%, 5%	2	3812
	SBD-A1-R025	25	Aluchrom Alloy	0.25mm	1%, 2%, 5%	2	3812
	SBD-C-R002	2	Copper Manganese 38 Alloy	0.46mm	1%, 2%, 5%	5	4525
	SBD-C-R003	3	Copper Manganese 38 Alloy	0.31mm	1%, 2%, 5%	5	4525
	SBD-CM-R005	5	Copper Manganese 43 Alloy	0.21mm	1%, 2%, 5%	5	4525
	SBD-A1-R010	10	Aluchrom Alloy	0.34mm	1%, 2%, 5%	5	4525
	SBD-A1-R015	15	Aluchrom Alloy	0.23mm	1%, 2%, 5%	5	4525

SBE							
	Type	Resistance (m Ohm)	Material	Thickness	Tolerance	Power (W)	SIZE
	SBE-CM-R0003	0.3	Copper Manganese 43 Alloy	1.42mm	1%, 3%, 5%	5	3820
	SBE-CM-R0005	0.5	Copper Manganese 43 Alloy	0.86mm	1%, 3%, 5%	5	3820
	SBE-A1-R001	1	Aluchrom Alloy	1.36mm	1%, 3%, 5%	5	3820
SBE-A1-R002	2	Aluchrom Alloy	0.68mm	1%, 3%, 5%	4	3820	

SBF							
	Type	Resistance (m Ohm)	Material	Thickness	Tolerance	Power (W)	SIZE
	SBF-C-R0002	0.2	Copper Manganese 38 Alloy	1.42mm	1%, 5%	5	3920
	SBF-MC2-R0002	0.2	MC2	1.42mm	1%, 5%	5	3920
	SBF-CM-R0003	0.3	Copper Manganese 43 Alloy	1.42mm	1%, 5%	5	3920
	SBF-CM-R0005	0.5	Copper Manganese 43 Alloy	0.84mm	1%, 5%	5	3920
	SBF-CM-R0007	0.7	Copper Manganese 43 Alloy	0.60mm	1%, 5%	5	3920
	SBF-CM-R001	1	Copper Manganese 43 Alloy	0.42mm	1%, 5%	4	3920
	SBF-A1-R001	1	Aluchrom Alloy	1.34mm	1%, 5%	5	3920
	SBF-A1-R0015	1.5	Aluchrom Alloy	0.89mm	1%, 5%	4.5	3920
	SBF-A1-R002	2	Aluchrom Alloy	0.67mm	1%, 5%	4	3920
	SBF-A1-R0025	2.5	Aluchrom Alloy	0.53mm	1%, 5%	3.5	3920
	SBF-A1-R003	3	Aluchrom Alloy	0.44 mm	1%, 5%	3	3920
	SBF-A1-R004	4	Aluchrom Alloy	0.33 mm	1%, 5%	2.5	3920
	SBF-A1-R005	5	Aluchrom Alloy	0.27 mm	1%, 5%	2	3920

SBG							
	Type	Resistance (m Ohm)	Material	Thickness	Tolerance	Power (W)	SIZE
	SBG-C-R0005	0.5	Copper Manganese 38 Alloy	0.59mm	1%, 2%, 5%	5	2725
	SBG-CM-R001	1	Copper Manganese 43 Alloy	0.33mm	1%, 2%, 5%	5	2725
	SBG-A1-R002	2	Aluchrom Alloy	0.53mm	1%, 2%, 5%	5	2725
	SBG-A1-R003	3	Aluchrom Alloy	0.35mm	1%, 2%, 5%	3	2725
SBG-A1-R005	5	Aluchrom Alloy	0.21mm	1%, 2%, 5%	2	2725	

SBZ							
	Type	Resistance (m Ohm)	Material	Tolerance	Power (W)	SIZE	
	SBZ-CM-R00005-8518	0.05	Copper Manganese 43 Alloy	5%	36	8518 (metric)	
	SBZ-CM-R0001-8518	0.1	Copper Manganese 43 Alloy	5%	36	8518 (metric)	
	SBZ-CM-R000125-8518	0.125	Copper Manganese 43 Alloy	5%	36	8518 (metric)	
	SBZ-CM-R0002-8518	0.2	Copper Manganese 43 Alloy	5%	36	8518 (metric)	
	SBZ-CM-R00025-8518	0.25	Copper Manganese 43 Alloy	5%	36	8518 (metric)	
	SBZ-CM-R00005-8420	0.05	Copper Manganese 43 Alloy	5%	36	8420 (metric)	
	SBZ-CM-R0001-8420	0.1	Copper Manganese 43 Alloy	5%	36	8420 (metric)	
	SBZ-CM-R0002-8420	0.2	Copper Manganese 43 Alloy	5%	36	8420 (metric)	
	SBZ-CM-R00025-8420	0.25	Copper Manganese 43 Alloy	5%	36	8420 (metric)	
	SBZ-A1-R0005-8420	0.5	Aluchrom Alloy	5%	36	8420 (metric)	
	SBZ-A1-R001-8420	1	Aluchrom Alloy	5%	-	8420 (metric)	